Г	1	2	3	4	5	6	7	8
А								
Б —								
С								
				CONTEXTEN	AL WATER MANAG	MENT INSTITUTE		
D			LOCATION ISSUE DATE	: 127, SUNIL MA : 05.03.2023	WATHA, BATTARA	MULLA. 10120		
E								

_

F

G

9 10



-	1	2	3	4	5	6	7	8
А								
в								
				Dra	wina List			
				Drawing Number	Drawir	ig Name		
С				S00	COVER PAGE			
				S000				
				501				
				502 503				
				505 504				
				<u> </u>	SECTIONS			
				<u> </u>)1		
D				S07	SECTION DETAIL 2	2		
				S08	BASE PLATE DETA	 NL		
				S09	FOOTING DETAIL			
				S10	SLAB REINFORCE	MENT		
E								
F								

G

9	10



1 2 3 4 5 6 7 8 9 10										
	1	2	3	4	5	6	7	8	9	10

Α GENERAL NOTS 4.5 1. ALL THE DIMENSIONS ARE IN mm AND LEVEL ARE IN METER UNO 1.2 THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS, ANY DISCREPANCIES TO BE BROUGHT TO THE ATTENTION OF THE RELEVANT ENGINEER ALL MATERIALS AND WORKMANSHIP TO BE IN ACCORDANCE WITH THE SPECIFICATIONS 1.3 AND RELEVENT SRI LANKAN, BRITISH AND EUROPEAN STANDARDS/CODES OF PRACTICE. 2. CONCRETE WORK ALL CONCRTE WORK SHALL BE IN ACCORDANCE WITH BS 8110, BS 8007 AND 2.1 SPECIFICATIONS. В CONCRTE TESTING SHALL BE IN ACCORDANCE WITH BS 5328, UNLESS OTHERWISE 2.2 3X10 SPECIFIED. 2.3 ALL CONCRTE SHALL BE READYMIX AND SUPPLIED ACCORDING TO THE APPROVED DESIGNED MIXES. ALL CONCRETE FOR REINFORCED CONCRETE WORK SHALL BE GRADE 30 AS PER DETAILED 2.4 DRAWING AND WITH MAXIMUM AGGREGATE SIZE 20mm UNLESS NOTED OTHERWISE MIX DESIGNS SHALL BE PREPARED AND SUBMITTED BY THE CONTRACTOR FOR APPROVAL 2.5 OF THE CONSULTANT THE CONTRACTOR SHALL SUBMIT RESULT OF TRIAL MIXES, GRADING CURVES AND ALL OTHER DETAILS TO ENABLE THE CONSULTANT TO EVALUATE THE PROPOSED MIX DESUGNS CONCRETE SHALL BE WELL COMPACTED BY MECHNICAL MEANS WITHOUT SEGREGATION. 2.6 2.7 CONCRETE GRADE AT THE COLUMN/BEAM JUNCTION TO BE EQUAL TO THE GRADE OF THE С COLUMN CONCRETE 5 2.8 ALL CONCRETE SURFACES, EXCEPT THOSE COVERED BY FORM WORK, SHALL BE CURED TO THE SATISFACTION OF THE CONSULTANT 2.9 ALL GRADE BEAMS AND SLABS SHALL BE FORMED ON SIDES UNLESS SHOWN OTHRWISE. 2.10 CONCRETING OF SLABS ON- GRADE (GROUND SLABS) SHALL BE PLACED IN BAYS WHERE LENGTHS AND WIDTHS DO NOT EXCEED SIX METERS UNLESS APPROVED BY THE 2. CONSULTANT 2.11 CONTRACTOR SHALL SUBMIT CONSTRUCTION JOINT LAYOUT, POURING PATTERN AND CASTING SEQUENCE FOR APPROVAL OF THE CONSULTANT AT LEAST EIGHT WEEKS BEFORE 3 THE POURING OF HE CONCRETE. 2.12 ALL BEAM VERTICAL CONSTRUCTION JOINTS SHALL BE MADE AT ONE THIRD OF THE SPAN POINTS USING VERTICAL BULKHEADS WITH SHEAR KEYS AND DOWELS (WHEN A SECONDARY BEAM INTERSECTS A PRIMARY BEAM AT THIS PONIT, THE JOINT IN THE D PRIMARY BEAM SHALL BE OFFSET A DISTANCE EQUAL TO TWICE THE WIDTH OF THE BEAM) THE LOCATION OF CONSTRUCTION JOINTS SHALL BE APPROVED BY THE CONSULTANT. 2.13 HORIZONTAL CONSTRUCTION JOINTS SHALL BE PERMITTED ONLY WHERE SHOWN ON THE STRUCTURAL DRAWINGS OR APPROVED BY THE CONSULTANT. HORIZONTAL OR NEARLTY HORIZONTAL JOINTS SHALL BE PREPARED BY ROUCHENING THE SURFACE IN AN APPROVED MANNER SO THAT THE AGGREGATES ARE EXPOSED UNIFORMLY, LEAVING NO LAITANCE, LOOSE PARTICLES OR DAMAGED CONCRETE. 2.14 EXCEPT AS DETAILED ON STRUCTURAL DRAWINGS, NO SLABS, OR BEAMS, SHALL BE SLEEVED FOR PIPING OR DUCTS, UNLESS APPROVED BY THE CONSULTANT. 2.15 MINIMUM FREE FALL OF CONCRETE SHOULD BE LIMITED TO 1.5m DURING THE PLACEMENT OF CONCRETE.IN THE EVENT LIFT HEIGHT IS GREATER THAN 1.5m TREMIE PIPE OR SIMILAR APPROVED ARRANGEMENT SHOULD BE USED. CASTING OF COLUMNS TOGETHER WITH SLABS AND BEAMS WILL NOT BE ALLOWED. Е 3. FORMWORK 3.1 ALL FORM SHALL COMPLY WITH BS 8110 AND BS 5975. 3.2 DO NOT REMOVE FORM WORK OR PROPS BEFORE CONCRETE GAINS SUFFICIENT STRENGTH SPECIFIED IN THE RLEVENT STANDARDS, UNDER ANY CIRCUMSTANCE A. MAINTAIN ALL FORM WORKS FOR BEAMS FOR A MINIMUM OF 7 DAYS. B. MAINTAIN ALL PROPS FOR ADITIONAL 14 DAYS MAINTAIN COLUMN FORM WORK FOR A MINIMUM OF 1 DAAY IF A SPECIAL CURING PROCEDURE IS NOT USED. REINFORCEMENT STEEL NOTES 4 4.1 ALL REINFORCING STEEL SHALL BE COMPLY WITH EN 10080;2005 GRADE 500Mpa DEFORMED TYPE B BARS. USE OF REINFORCEMENT FOR THE WORK WILL BE CONSISERED ONLY UPON SUBMITTAL OF RELEVENT INFORMATION TO THE CONSULTANT FOR APPROVAL, SUBMITTALS SHALL INCLUDE MILL CERTIFICATES INDICATING THE MATERIAL COMPOSITION, YEILD STRENGTH, ULTIMATE STRENGTH, AND BAR BEND TEST 4.2 NO REINFORCING BARS SHALL BE WELDED, UNLESS SPECIFICALLY NOTED OR APPROVED BY THE CONSULTANT. CONCRETE COVER OF REINFORCEMENT TO BE:- Cnom INTERNAL FACE 35mm AND 4.3 EXTERNAL FACE 50mm LAP LENGTH FOR REINFORCEMENT (UNO) H12=550mm, H16=720mm, H20=900mm 4.4 H25=1125mm, H32=1450mm, H40=1800mm

G

LEGE	ND	
V H FF EF SB SSL TOB BOC CJ		VERTICAL HORIZONTAL NEAR FACE FAR FACE EACH FACE SIDEBARS STRUCTURAL SLAB LEVEL TOP OF BEAM BOTTOM OF CONCRETE CONSTRUCTION JOINT
H32-01-1	00	SPACING OF BAR BAR MARK REFERENCE DIA. OF BAR GRADE OF STEEL OLIANTITY OF BAR

4.6 NO CONCRETE IS TO BE POURED UNTIL THE REINFORCEMENT HAS BEEN INSPECTED AND APPROVED BY THE ENGINEER.

MULTIPLIES

- 4.7 MINIMUM ANCHORING LENGTH SHOULD BE 450mm.
- BRICK WALLS/LINTEL BEAMS
 - IN THE ERECTION OF BRICK OR BLOCK WALLS. A LIGHT GAUGE WIRE MESH OR PREFERABLY AN EXPANDED METAL (COIL MESH) TO BS EN 10142, SHOULD BE LAID IN EVERY FOURTH COURSE OF BRICK OR BLOCK LAYING, MESH SHOULD ALSO BE FIXED AT LOCATIONS IN CONTACT WITH A CONCRETE SURFACE SUCH AS COLUMNS OR BEAMS
- ALL BLOCK/ BRICK WALLS SHALL BE TIED WITH CONCRETE STIFFNER COLUMNS AND BEAMS
- ALL OPENINGS (DOOR/WINDOW) SHALL BE STIFFEN WITH STIFFNER COLUMSNAND LINTEL BEAMS.

STRUCTURAL STEEL

- THE STRUCTURAL STEELWORKS SHOWN ON THE DRAWINGS HAS BEEN DESIGNED TO EN1993-1:1
- 2. UNLESS OTHERWISE SPECIFIED, ALL STEEL MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT.
- 3. ALL SET SCREW, NUT AND WASHERS ARE COMPLYING WITH DIN933 OR EQUIVALENT.
- 4. ALL GRADE 8.8 BOLTS SHALL COMPLY EN ISO 898-1 & ALL SET SCREW, NUT AND ASHERS ARE COMPLY WITH DIN 933 OR EQUIVALENT.
- 5. ALL WELDS SHALL COMPLY WITH BS EN 1011-14 & BS EN1011-2.
- 6. SURFACE TREATMENT
- 61 THE STEEL MEMBERS SHOULD BE SAND BLASTED, WIRE BRUSHED AND CLEANED TO REMOVE MILL SCALE DIRT AND GREASE. THE COATING SYSTEM SHOULD BE COMPLIED WITH THE BS EN ISO 12944-5:2018 6.2
- AND THE MINIMUM DFT SHOULD NOT BE LESS THAN 240µr 7. CONSIDERATION SHALL BE GIVEN TO TESTABILITY AND SAFETY OF STEEL FRAMEWORK DURING ERECTION.THE CONTRACTOR SHALL ENSURE THAT THE STRUCTURE IS NOT
- SUBJECTED TO EXCESSIVE DEFLECTION OR STRESS DURING ERECTION. 8. ALL DIMENSIONS AND DETAILS TO BE VERIFIED ON SITE AND CHECKED BY THE
- CONTRACTOR ARCHITECTURAL DRAWINGS AND ANY DISCREPANCIES SHOULD BE REPORTED IN ADVANCE
- 9. PROPRIETARY NON-SHRINK GROUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 60N/mm² AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT OF STEEL FRAME/COLUMN.
- 10 TECHNICAL DETAILS INCLUDING MILL CERTIFICATES OF STRUCTURAL STEEL SET SCREWS, NUTS, ANCHOR BOLTS, DECKING SHEETS, SHEAR STUDS ETC, TO BE FORWARDED TO ENGINEER BY CONTRACTOR PRIOR TO FABRICATION OF STRUCTURAL STEEL WORKS
- 11. CONTRACTOR TO PREPARE SHOP DRAWINGS AND FORWARDED TO ENGINEER FOR VERIFICATION AND APPROVAL PRIOR TO FABRICATION OF STRUCTURAL STEEL WORKS.
- 12. CONTRACTOR IS REQUIRED TO PERFORM TESTS TO VERIFIED STRUCTURAL STRENGTH/WELDING QUALITY AND DRY FILM THICKNESS OF THE PAINT, PULL OUT AND BENDING TEST OF SHEAR STUDS AS PER ENGINEER'S DIRECTIONS.

13. ABBREVIATIONS

- ASP AS PER THE SPECIFICATION THK - THICKNESS
- - FW FILLET WELD
 - DIAMETER ø RHS - RECTANGULAR HOLLOW SECTION
 - SHS SQUARE HOLLOW SECTION
 - PL PLATE

14. ALL THE DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED

SPECIAL NOTE

IN CASE OF DISCREPANCIES BETWEEN THIS GENERAL NOTES DRAWING AND ANY NOTES ON INDIVIDUAL DRAWINGS, THE NOTES ON INDIVIDUAL DRAWING TAKE PRCEDENCE.

)5/03/23	AQ	AP	AP	PAK
Issue	Date	Detail	Design	Chkd	Apprd
Client	Duto	Dotai	D doigit	Onixa	, thbi a
	Interna	tional w	ator Mar	aament	
International Water Management Institut	Instituti	on (IWN	11)	ayment	
	127, Su Battara	unil Maw mulla, 1	atha, 0120.		
S S	HERA	N HE	NRYA	\$ \$ 0 0	CIATES
Cł 25	artered /3, Lau	Archit	ects/De ad, Co	signers lombo 4	
Te	1. 2591	277	Fax.	5336694	
Structu	ral Engi	neer			
		NOVATI	/E STRUC	TURES	DESIGN
	GI	ROUP (P	VT) LTD. CTURAL EN	GINEERING	SERVICE
	NO W	O 25/A, D estern,	elathura, 、	Ja-Ela,	
ISD		i Lanka I : +9	94(0)77-74	18-7220	
CONSULTING AND ENGINEERIN	NG SERVICE W	eb :wi	ww.isdg.lk		
Ma ati	, 			_	
weetii	ng Roo	om Ex	tentior	1	
Drawing	Title				
GENE		NOTE			
Scale at	A3				
Plot ID					
Drawing	Status				
Informatio	on				
Job No	Drawing) No			Issue
J010	ISDG/	IWMI/JO	10-2023	3- S01	



9 10 THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD.THIS DOC'S STRICTLY PRIVATE.CONFIDENTIAL AND PERSONAL TO ITS REC AND SHOULD NOT BE COFIED, DISTRIBUTED OR REPRODUC IN WHOLE OR PART, NOT PASSED TO ANY THIRD PARTY. TENDER NOTES . THESE DRAWINGS ARE PRELIMINARY DRAWINGS ISSUED FOR TENDERING PURPOSES ONLY AS AN INDICATION OF THE EXTENT OF WORKS. THEY ARE NOT A COMPLETE SET OF CONSTRUCTION DRAWINGS AND ARE NOT TO BE USED FOR CONSTRUCTION. . TO DETERMINE THE FULL EXTENT OF WORK THESE DRAWINGS SHALL BE READ IN CONJUNCTION WITH THE ARCHITECTURAL DRAWINGS AND OTHER CONTRACT DOCUMENTS. SHOULD ANY AMBIGUITY, ERROR, OMMISION, DISCREPANC, INCONSISTENCY OR OTHER FAULT EXIST OR SEEM TO EXIT IN THE DOCUMENT, IMMEDIATELY NOTIFY, IN WRITING TO THE SUPERINTDENDENT. 05/03/23 AQ AP AP PAK Issue Date Detail Design Chkd Apprd Client International water Managment Institution (IWMI) 127. Sunil Mawatha. Battaramulla, 10120. SHERAN HENRY ASSOCIATES Chartered Architects/Designers 25/3, Lauries Road, Colombo 4 Tel. 2591277 Fax. 5336694 Structural Engineer INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. CIVIL / STRUCTURAL ENGINEERING SERVICE NO 25/A, Delathura, Ja-Ela, KONCHEAR ENGREGA ENERGY KONCHEAR ENGREGA ENERGY KONCHEAR ENGREGA ENERGY Keb : WWW.isdg.lk Job Title Meeting Room Extention Drawing Title FOUNDATION LAYOUT Scale at A3 1:100 Plot ID Drawing Status Information Job No Drawing No Issue J010 ISDG/IWMI/J010-2023- S04



9	10
	THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. THIS DOCUMENT IS STRUCTLY PRIVATE.CONFIDENTIAL AND PERSONAL TO ITS RECIPENTS AND SHOULD NOT BE COMED. DISTRIBUTED OR REPRODUCED IN WHOLE OR PART, NOT PASSED TO ANY THIRD PARTY.
	GENERAL NOTE
	 ALL DIMENSION ARE IN mm UNLESS NOTED OTHERWISE.
	2. ALL THE STRUCTURAL DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVENT ARCHITECTURAL DRAWING.
	3. THE STRUCTURAL STEELWORKS SHOWN ON THE DRAWINGS HAS BEEN DESIGNED TO EN1993-1:1.
	4. UNLESS OTHERWISE SPECIFIED, ALL STEEL MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT.
	5. ALL SET SCREW, NUT AND WASHERS ARE COMPLYING WITH DIN933 OR EQUIVALENT.
	 ALL GRADE 8.8 BOLTS SHALL COMPLY EN ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 OR EQUIVALENT.
	 ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2.
	8. PROPRIETARY NON-SHRINK GROUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT OF STEEL FRAME/COLUMN.
	9. ABBREVIATIONS
	APS - AS PER SPECIFICATION THK - THICKNESS
	PW - FILLET WELD RHS - RECTANGUALR HOLLOW SECTION PL - PLATE Ø - DIAMETER
	Client International water Managment Institution (IWMI) 127, Sunil Mawatha, Battaramulla, 10120.
	SHERAN HENRYASSOCIATES
	Chartered Architects/Designers 25/3, Lauries Road, Colombo 4 Tel. 2591277 Fax. 5336694
	Structural Engineer INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. CIVIL / STRUCTURAL ENGINEERING SERVICE NO 25/A, Delathura, Ja-Ela, Western, Sri Lanka Tel : ±94(0)77-748-7220 Web : WWW.isdg.lk
	Job Title Meeting Room Extention
	Drawing Title
	COLUMN LAYOUT
	Scale at A3 1 : 100 Plot ID
	Drawing Status
	Information
	J010 ISDG/IWMI/J010-2023- S02



9	10
	THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. THIS DOCUMENT IS STRUCTLY PRIVATE.COMFIDENTIAL AND PERSONAL TO ITS RECIPENTS AND SHOULD NOT BE COMFED. DISTRIBUTED OR REPRODUCED IN WHOLE OR PART, NOT PASSED TO ANY THIRD PARTY.
	GENERAL NOTE
	 ALL DIMENSION ARE IN mm UNLESS NOTED OTHERWISE.
	2. ALL THE STRUCTURAL DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVENT ARCHITECTURAL DRAWING.
	3. THE STRUCTURAL STEELWORKS SHOWN ON THE DRAWINGS HAS BEEN DESIGNED TO EN1993-1:1.
	4. UNLESS OTHERWISE SPECIFIED, ALL STEEL MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT.
	5. ALL SET SCREW, NUT AND WASHERS ARE COMPLYING WITH DIN933 OR EQUIVALENT.
	 ALL GRADE 8.8 BOLTS SHALL COMPLY EN ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 OR EQUIVALENT.
	 ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2.
	8. PROPRIETARY NON-SHRINK GROUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT OF STEEL FRAME/COLUMN.
	9. ABBREVIATIONS
	APS - AS PER SPECIFICATION THK - THICKNESS FW - FILLET WELD
	RHS - RECTANGUALR HOLLOW SECTION PL - PLATE
	05/03/23 AQ AP AP PAK
	Issue Date Detail Design Chkd Apprd
	Client
	Institution (IWMI) 127, Sunil Mawatha,
	Battaramulla, 10120.
	SHERAN HENRY ASSOCIATES
	25/3, Lauries Road, Colombo 4 Tel. 2591277 Fax. 5336694
	Structural Engineer
	GROUP (PVT) LTD. CIVIL / STRUCTURAL ENGINEERING SERVICE
	NO 25/A, Delathura, Ja-Ela, Western, Sri Lanka
	Сандами и и выясяяя зиня Web : www.isdg.lk
	Job Title
	weeting Room Extention
	Drawing Title
	BEAM LAYOUT
	Scale at A3
	1 : 100 Plot ID
	Drawing Status
	Job No Drawing No
	J010 ISDG/IWMI/J010-2023- S03



9	10
	THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD.THIS DOCUMENT IS STRICTLY PRIVATE.CONFIDENTIAL AND PERSONAL TO ITS RECIPIENTS AND SHOULD NOT BE COPIED, DISTRIBUTED OR REPRODUCED IN WHOLE OR PART, NOT PASSED TO ANY THIRD PARTY.
	GENERAL NOTE
	1. ALL DIMENSION ARE IN mm UNLESS NOTED OTHERWISE.
	 ALL THE STRUCTURAL DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVENT ARCHITECTURAL DRAWING.
	 THE STRUCTURAL STEELWORKS SHOWN ON THE DRAWINGS HAS BEEN DESIGNED TO EN1993-1:1.
	4. UNLESS OTHERWISE SPECIFIED, ALL STEEL MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT.
	5. ALL SET SCREW, NUT AND WASHERS ARE COMPLYING WITH DIN933 OR EQUIVALENT.
	 ALL GRADE 8.8 BOLTS SHALL COMPLY EN ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 OR EQUIVALENT.
	 ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2.
	 PROPRIETARY NON-SHRINK GROUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT OF STEEL FRAME/COLUMN.
	9. ABBREVIATIONS
	APS - AS PER SPECIFICATION THK - THICKNESS
	FW - FILLE1 WELD RHS - RECTANGUALR HOLLOW SECTION PL - PLATE Ø - DIAMETER
	05/03/23 AQ AP AP PAK
	Issue Date Detail Design Chkd Apprd
	Client International water Managment
	127, Sunil Mawatha,
	SHERAN HENRYASSOCIATES Chartered Architects/Designers 25/3, Lauries Road, Colombo 4 Tel. 2591277 Fax. 5336694
	Structural Engineer INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD.
	25/A, Delathura, Ja-Ela, Western Province, Sri Lanka. Tel :+94(0)77-748-7220 Web : www.isdn.kk
	Job Title
	Meeting Room Extention
	Drawing Title
	SECTIONS
	Scale at A3
	Plot ID
	Drawing Status
	Information
	Job No Drawing No Issue J010 ISDG/IWMI/J010-2023- S05



9	10
	THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD.THIS DOCUMENT IS STRUCTLY PRIVATE, CONFIDENTIAL AND PERSONAL TO ITS RECIPIENTS AND SHOULD NOT BE COPIED, DISTRIBUTED OR REPRODUCED IN WHOLE OR PART, NOT PASSED TO ANY THIRD PARTY.
	GENERAL NOTE
	1. ALL DIMENSION ARE IN mm UNLESS NOTED OTHERWISE.
	2. ALL THE STRUCTURAL DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVENT ARCHITECTURAL DRAWING.
	3. THE STRUCTURAL STEELWORKS SHOWN ON THE DRAWINGS HAS BEEN DESIGNED TO EN1993-1:1.
	4. UNLESS OTHERWISE SPECIFIED, ALL STEEL MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT.
	5. ALL SET SCREW, NUT AND WASHERS ARE COMPLYING WITH DIN933 OR EQUIVALENT.
	6. ALL GRADE 8.8 BOLTS SHALL COMPLY EN ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 OR EQUIVALENT.
	 ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2.
	8. HIGH STRENGTH GROUT WITH A MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT OF STEEL COLUMN.
	9. ABBREVIATIONS
	APS - AS PER SPECIFICATION THK - THICKNESS FW - FILLET WELD RHS - RECTANGUALR HOLLOW SECTION PL - PLATE Ø - DIAMETER
	05/03/23 AQ AP AP PAK
l	Issue Date Detail Design Chkd Apprd
$\left\{ \right\}$	International water Managment Institution (IWMI) 127, Sunii Mawatha, Battaramulla, 10120.
	SHERAN HENRYASSOCIATES Chartered Architects/Designers 25/3, Lauries Road, Colombo 4 Tel. 2591277 Fax. 5336694
_ 1	Structural Engineer INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. CIVIL / STRUCTURAL ENGINEERING SERVICE NO 25/A, Delathura, Ja-Ela, Western, Sr Lanka Tel : +94(0)77-748-7220 Web : www.isdg.lk
	Job Title Meeting Room Extention
5	Drawing Title
5	SECTION DETAIL 01
	Scale at A3 As indicated Plot ID
	Drawing Status Information
	Job No Drawing No Issue





THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD.THIS DO IS STRICTLY PRIVATE.CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND PERSONAL TO ITS RE AND SNOULD NOT BE CONFIDENTIAL AND THE DE READ OTHER WISE. 2. ALL THE STRUCTURAL DRAWING SHOUL BE READ IN CONJUNCTION WITH RELEV ARCHITECTURAL DRAWING. 3. THE STRUCTURAL STEELWORKS SHOW ON THE DRAWINGS HAS BEEN DESIGNE TO EN1993-1:1. 4. UNLESS OTHERWISE SPECIFIED, ALL ST MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT. 5. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALE 6. ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-18 ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. 7. ALL WELDS SHALL COMPLY WITH DIN 933 O EQUIVALENT. 7. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. 8. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. 9. ABBREVIATIONS APS - AS PER SPECIFICATION	DCUN ECIP JCEI Y.
 GENERAL NOTE ALL DIMENSION ARE IN mm UNLESS NO OTHERWISE. ALL THE STRUCTURAL DRAWING SHOUL BE READ IN CONJUNCTION WITH RELEV ARCHITECTURAL DRAWING. THE STRUCTURAL STEELWORKS SHOW ON THE DRAWINGS HAS BEEN DESIGNE TO EN1993-1:1. UNLESS OTHERWISE SPECIFIED, ALL ST MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALE ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	
 ALL DIMENSION ARE IN mm UNLESS NO OTHERWISE. ALL THE STRUCTURAL DRAWING SHOUL BE READ IN CONJUNCTION WITH RELEV ARCHITECTURAL DRAWING. THE STRUCTURAL STEELWORKS SHOW ON THE DRAWINGS HAS BEEN DESIGNE TO EN1993-1:1. UNLESS OTHERWISE SPECIFIED, ALL ST MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALENT. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALENT. ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT HDIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	
 ALL THE STRUCTURAL DRAWING SHOUL BE READ IN CONJUNCTION WITH RELEV ARCHITECTURAL DRAWING. THE STRUCTURAL STEELWORKS SHOW ON THE DRAWINGS HASS BEEN DESIGNE TO EN1993-1:1. UNLESS OTHERWISE SPECIFIED, ALL ST MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALE ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION)TE
 THE STRUCTURAL STEELWORKS SHOW ON THE DRAWINGS HAS BEEN DESIGNE TO EN1993-1:1. UNLESS OTHERWISE SPECIFIED, ALL ST MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALE ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	LD 'EN
 UNLESS OTHERWISE SPECIFIED, ALL ST MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT. ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALE ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	/N D
 ALL SET SCREW, NUT AND WASHERS AF COMPLYING WITH DIN933 OR EQUIVALE ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	ΓEE
 ALL GRADE 8.8 BOLTS SHALL COMPLY E ISO 898-1 & ALL SET SCREW, NUT AND WASHERS ARE COMPLY WITH DIN 933 O EQUIVALENT. ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	RE NT
 ALL WELDS SHALL COMPLY WITH BS EN 1011-4 & BS EN1011-2. PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	EN DR
 PROPRIETARY NON-SHRINK GROUT WIT MINIMUM COMPRESSIVE STRENGTH OF 60N/mm2 AT 28 DAYS SHOULD BE USED AFTER THE ERECTION AND ALIGNMENT STEEL FRAME/COLUMN. ABBREVIATIONS APS - AS PER SPECIFICATION 	1
9. ABBREVIATIONS APS - AS PER SPECIFICATION	TH .
APS - AS PER SPECIFICATION	
I HK - THICKNESS FW - FILLET WELD RHS - RECTANGUALR HOLLOW SECTION PL - PLATE	N
Issue Date Detail Design Chkd App	ord
Client INFRAME International water Managment Institution (IWMI) 127, Sunil Mawatha, Battaramulla, 10120.	
SHERAN HENRY ASSOCIAT	 T F
Chartered Architects/Designers 25/3, Laurise Road, Colombo 4 Tel. 2591277 Fax. 5336694	
Structural Engineer INDOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. CIVIL STRUCTURAL ENGINEERING SERVIN NO 25/A, Delathura, Ja-Ela, Western, Sr Lanka Tel : +94(0)77-748-7220 Web : www.isdg.lk	N
Job Title Meeting Room Extention	
Drawing Title BASE PLATE DETAIL Scale at A3 As indicated	
Plot ID	
Drawing Status	
Information	
Job No Drawing No	

9



	9		10
	9	INNOVATIVE BI IS STRICTLY PR AND SHOU IN WHO GENERAL 1. ALL DIP OTHER 2. ALL THE BE REA ARCHIT 3. THE RE ON THE TO EN1 4. CONCR BE:- Cric EXTERN 5. THE GR UNLESS	10 DRAWING AND DESIGN ARE PATENTED WITH TRUSTINGE BESIGN SPROIP IPYT I TO THIS DOCUMENT INTECONFIDENTIAL AND PERSONAL TO ITS RECIPIENTS INTO TE COOPERD. DISTIBUTION OR REPRODUCED LE OR PART, NOT PASSED TO ANY THIRD PARTY. INTO ENTE MENSION ARE IN mm UNLESS NOTED WENSION ARE IN mm UNLESS NOTED WISE. E STRUCTURAL DRAWING SHOULD D IN CONJUNCTION WITH RELEVENT ECTURAL DRAWING. INFORCED CONCRETE WORKS SHOWN DRAWINGS HAS BEEN DESIGNED 992-1:1. ETE COVER OF REINFORCEMENT TO DM INTERNAL FACE 35mm AND VAL FACE 50mm ADE OF CONCRTE TO BE C25/30 SOTHER WISE NOTED.
		05	103/23 AQ AP AP PAK
		Issue D Client With the second Building the second Client Client Magnetic the second Client S H Chan Chan Chan Chan Chan Chan Chan Chan	ate Detail Design Chkd Apprd International water Managment Institution (IWMI) I27, Sunil Mawatha, Battaramulla, 10120. ERAN HENRY ASSOCIATES Interest Architects/Designers
ates to Lettered Grids ates to Numbered Grids		Structura	, Lauries Road, Colombo 4 . 2591277 Fax. 5336694 I Engineer INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. CIVIL / STRUCTURAL ENGINEERING SERVICE NO 25/A, Delathura, Ja-Ela, Western, Sri Lanka Tel :+94(0)77.748-7220 Web : www.isdg.lk
STARTERS		Job Title Meeting	g Room Extention
С	MK D		
25 07	8H08 08 200	Scale at A	3 d
25 07	8H08 08 200	Plot ID Drawing S	tatus
25 07	8H08 08 200	Information Job No D	rawing No Issue
		3010	102 3/1441411/30 10-2023- 308



9	10		
	THIS DRAWING AND DESIGN ARE PATENTED WITH INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD.THIS DOCUMENT IS STRICTLY PRIVATE,CONFIDENTIAL AND PERSONAL TO IST RECIPIENTS AND SHOULD NOT BE COPIED, DISTRIBUTED OR REPRODUCED IN WHOLE OR PART, NOT PASSED TO ANY THIRD PARTY. GENERAL NOTE		
	1. THE COMPOSITE BEAMS AND BONDECK SLABS SHOWN ON THE DRAWINGS HAS BEEN DESIGN TO BS EN 1994-1-1.		
	2. UNLESS OTHERWISE SPECIFIED ALL BARE STEEL MEMBERS SHALL BE OF GRADE S 275 COMPLYING TO BS EN 10025-2 OR EQUIVALENT.		
S THROUGH	3. CONCRETE GRADE C25/30 SHOULD BE USED FOR BONDECK SLAB.		
	PROFILE DECKING SHEET		
ED DECKING SHEET	1. DECKING SHEETS SHOULD BE HOT DIPPED ZINC COATED HIGH STRENGTH WITH MINIMUM 550 MPA YIELD STRENGTH AND COATING MASS OF Z 275 (MIN 275 g/m ² TOTAL OR ZINC COATING ON BOTH SIDES).		
	2. ALL THE PROFILE DECKING SHEETS SHOULD BE COMPLIANCE TO BS EN 10147 : 2000.		
	STUD & STUD THROUGH WELDING DECK		
	1. ALL STUDS SHOULD BE LOW CARBON STEEL, WITH A MINIMUM YIELD STRENGTH OF 350 N/mm ² AND MINIMUM TENSILE STRENGTH OR 450 N/mm ² IN ACCORDANCE WITH BS EN ISO 13918		
	2. DRAWN ARC STUD WELDING PROCESS MUST BE FOLLOWED FOR THE STUD WELDING		
kg/m/	3. ALL THE STUD WELDING SHOULD BE COMPLIANCE TO EN ISO 14555 : 247 ARC STUD WELDING OR METALIC MATERIALS		
	4. TOP FLANGES OF BEAMS MUST BE UNPAINTED, WHERE THE STUDS ARE TO BE WELDED.		
	5. THE BEAMS SHOULD BE FREE OF DIRTS SAND AND OTHER MATERIALS		
	6. THE BEAMS SHOULD BE FREE OF HEAVY RUST AND MILL SCALE		
	05/03/23 AQ AP AP PAK		
	Issue Date Detail Design Chkd Apprd		
	International water Managment Institution (IWMI) 127, Sunil Mawatha, Battaramulla, 10120.		
	SHERAN HENRY ASSOCIATES Chartered Architects/Designers 25/3, Lauries Road, Colombo 4 Tel. 2591277 Fax. 5336694		
	Structural Engineer INNOVATIVE STRUCTURES DESIGN GROUP (PVT) LTD. CIVIL / STRUCTURAL ENGINEERING SERVICE NO 25/A, Delathura, Ja-Ela, Western, Sri Lanka		
	Синдание выявляет теля : +94(0)77-748-7220 Синдание выявляет Web : www.isdg.lk		
	Job Title Meeting Room Extention		
	Drawing Title		
	SLAB REINFORCEMENT		
	Scale at A3 As indicated		
	Plot ID		
	Drawing Status Information		
	Job No Drawing No Issue J010 ISDG/IWMI/J010-2023- S10 Issue		